


| | GLMF-400W FOLDABLE MEDICAL LIGHT | | | | |
|-----------------|----------------------------------|---------|---------|--------|--|
| | PROJECT: | | | | |
| | NOTE: | | | | |
| | COMPANY NAME: | | | | |
| | TYPE: | | | DATE: | |
| CATALOG NUMBER: | | | | | |
| ITEM CODE WATT | ССТ | CONTROL | VOLTAGE | OPTION | |

SPECIFICATION

| Light Source | LED |
|--------------------|------------------------------------|
| IP | IP65 |
| Chips | SAMSUNG LM301B |
| Wattage | 400W (4 full spectrum bars 400W) |
| Efficacy | 2.7 μmol/J |
| PPF | 1,080 µmol |
| Digital controller | RJ14 port |
| Relative Humidity | 23%RH-90%RH |
| Life-span | L85-50,000Hrs |
| CRI | 80Ra |
| Finish | Silver / Blue |
| Work Temperature | -25°C~+50°C |
| Certification | ETLc |
| Warranty | 5 years |

ITEM CODE

| ltem | Description |
|----------------|---|
| GLMF-400W-120V | Foldable Plant Light 4 strips, 400W, 5000K add 660nm,120V, Dimming for single fixture, RJ14 adaptor, 2.7 µmol/J |



FEATURES

CONSTRUCTION

- Light engines are made of extruded aluminum for better cooling
- Easily removable driver and light bars for maintenance capability
- Driver housing made of aluminium extrusion and can be installed remotely
- Multi-bar assembly unit, easy assembly and installation
- Driver compartment isolated from light engine for better cooling
- Ingress protection IP65
- Samsung LED chips LM301B
- Ambient temperature -20°C ~ +50°C

MOUNTING

 Suspension with stainless V hook for luminaire and driver box

CONTROL

 Optional digital controller with RJ14 cable connect to device

ELECTRICAL

 120/277Vac 60Hz standard, 347V optional

COMPLIANCE

- ETLc
- · ROHS
- CSA C22.2#250.0:2018 Ed.4

